

Automatic type Durometer Stand GX-610 II

Stable measurement without individual variability

Easy operation via touch panel display

Durometers* can be attached for GX-610II.

Stable measurement without individual variability

Constant speed and load provide stable measurement.

Easy to speed control

Compliant by JIS K 6253 and ISO 7619.
Moving-down speed range is 1.0 mm/sec to 20 mm/sec, with 0.1mm/ sec in steps.

■ Specification of GX-610II

Moving Speed	1.0 to 20.0 mm / sec (configurable every 0.1 mm / sec)
Consumption Current	1.0 (A) or less
Dimensions	W180 (not including SW protrusion) × L276 (not including connect protrusion) × H400 (to the pole tip) (mm)
Body Weight	11.4 (kg) / power supply 0.2 (kg)
Power Supply	Input AC100-240 (V)
Display Brightness	8 levels
Touch Sensitivity	Hi / Lo setting
Touch Sound	Enable / Not Enable
Suggested Price	¥363,000

VFD (Vacuum fluorescent display) touch panel
Calibrate certification is available



■ Weight for 5kg.
*option=ZY-128



■ Weight for 1kg.
*Included= ZY-089

- Type A/E Durometer need ZY-089(1kg).
- Type D need optional weight ZY-128(5kg).
- GSD series needs optional weight ZY-090(1kg).

■ Specification of weight

Pressure Value	Weight Code-No.	Applicable Durometer Models
1kg	Analog	ZY-089 (Included)
	Digital	ZY-090 (Option)
4kg		ZY-128 (Option)
		D, ASTM C, DO, JIS C (Old type)



Durometer

*The durometer in the photo is not Included.
*Some company's Durometer can not be used.