

WORLD'S FIRST!

Durometer with built-in Bluetooth

NEW GSB Series JIS/ISO compliant

The long-awaited Bluetooth-Durometer (Rubber hardness tester) is now available from Teclock, the No.1 manufacturer of Durometers.

Via Bluetooth the data can be sent with one push

Connect directly to a PC, smartphone, or tablet via Bluetooth, send data with one push.

Multifunctionality realized through integration with free app

As combined with **SmartMeasure™ Lite**, it is possible to monitor peak hardness values and changes over time.

Compliant with JIS K 6253, ISO 48, and ASTM D 2240

Type A and Type D are now available. More products will be added in the future.

■ Specification

	TypeA	TypeD
Minimum Indication unit	Hardness0.1	
Tolerance	Hardness±0.5	
Conform Standards	JIS K 6253/ ISO 48/ASTM D 2240	
Body Color	Blue Gray / Champagne Gold	
Spring Load value	550-8050mN (56.1-821.1gf)	0-44450mN (0-4533gf)
Pressurized Face	Square BaseW39xD16 / Round Base:Φ18	
Indenter height	2.50mm	
Bluetooth Transmission	Built-in (standard)	
Weight	Approx. 320g	



Free of charge App provided by Teclock

SmartMeasure™ Lite
for Durometer

No need to count seconds using a stopwatch!

Supports peak values and elapsed time measurements, which are important for rubber hardness measurement.

Timer A and B seconds can be set as desired!

i.g., Timer A 3seconds, Timer B 15seconds

Selectable Pressurized Face and Body Color



■ Lineup

Blue Gray

* Image is TypeA, Square Base

TypeA

Square Base **GSB-719N-BG**

Round Base **GSB-719R-BG**

List Price TBA

TypeD

Square Base **GSB-720N-BG**

Round Base **GSB-720R-BG**

List Price TBA

Champagne Gold

* Image is TypeD, Round Base

TypeA

Square Base **GSB-719N-CG**

Round Base **GSB-719R-CG**

List Price TBA

TypeD

GSB-720N-CG

Round Base **GSB-720R-CG**

List Price TBA

The contents are subject to change without notice.

